

*POWER*TOME≡3D™

Ideal for Applications In:

- 3D Array Tomography
- Brain Science
- Connectomics
- Morphological Studies
- Pathology
- Materials Research
- Failure Analysis

Designed for:

- Transmission Electron Microscopy
- Scanning Electron Microscopy
- Atomic Force Microscopy
- Scanning Probe Microscopy
- Optical Microscopy
- FTIR



The Million-Nanometer Ultramicrotome

The PT3D features a full 1 mm of advance, permitting uninterrupted, ultra thin, sectioning to a depth of one millimeter. This unique advantage is especially beneficial for 3D reconstruction work, array tomography, and any situation where high amounts of precision specimen trimming are involved.

The all-in-one computer controller features a slim design, touch screen control monitor, including wireless mouse & keyboard, interconnect cables & accessories. All control functions can be activated by touching the control monitor screen, or by mouse, while maintaining use of the tactile digital controller. The color monitor displays a bright and user-friendly control interface with intuitive control icons logically arranged around the video display.

Various add-on components for array tomography are available.

FEATURES

- Produce high quality semi- and ultra-thin sections for TEM, SEM, block facing for AFM, TOFSIMS, LM, and CEMOVIS.
- Hybrid control system includes touch screen monitor with Visutrac™ cutting zone control, plus digital tactile controller
- High-definition video package showing work area with built-in video measuring system
- Record & save video clips & still images
- Built-in report generator, database, & diagnostic routines for automatic documentation of sectioning parameters
- Ergonomic stereo microscope system with unique lateral viewing control
- Four Types of LED illumination are provided. All are independently adjustable.

Overhead bright diffuse LED Illumination

Backlighting for careful approach of the knife to the specimen

Transillumination through the specimen holder for viewing details of the specimen within the block

(Transillumination LED can also be used for spot illumination by pointing it towards the specimen or knife edge)

- Patented Power Drive© cutting stroke for large blocks & hard materials
- Electronic step advance for final specimen approach to the knife edge
- High stability mechanical advance system for reproducible section thickness
- Built-in calibration & service diagnostics instantly confirm functionality & simplify maintenance procedures

SPECIFICATIONS

- Specimen auto feed: 1 mm (1,000 µm; 1,000,000 nm)
- Section thickness: 0nm to 15µm
- Cutting speed: 0.1 to 100mm/sec in 0.1mm/sec increments
Variable return speed over entire cutting speed range
- Knife stage movement: 50mm gross advance
25mm E-W travel
12mm N-S advance

INCLUDES**Steremicroscope Trinoculars ACCU-SCOPE 3075 Series**

- 7:1 zoom
- 6.7x to 45x magnification
- 10x WF (22mm) eyepieces
- phototube with 50/50% right path
- c-mount camera adaptor
- 45-degree viewing angle

Teledyne 2.1 megapixel USB-C 3.1 color camera

- with Sony IMX327 Rolling Shutter Sensor

Accessory Kit

- Transilluminated Specimen Holders (Universal, 8mm Stepped, and 7mm Flat)
- Arc Segment Holder
- Arc Mounting Stub
- Trimming Block
- Trimming Post
- 12" Transillumination LED
- Cable, fuses, wrenches

ACCEPTS THE FOLLOWING KNIVES

- Glass knives up to 12mm wide
- Triangular tungsten carbide knives
- Any commercial brand of diamond knives

OPTIONAL ACCESSORIES AVAILABLE FOR PURCHASE

Room Temperature Specimen Holders

- Vise type flat specimen holder.
- Universal transilluminated specimen holder.
- 7mm flat specimen transilluminated holder.
- 5.6mm flat specimen transilluminated holder.

Other PowerTome Accessories

- Static Line Ionizer.
Ionization depolarization device, 115VAC or 220 - 240VAC.
- Breath shield, for knife stage.
- Water trough filler.
Includes reservoir/pump, tubing and filler tube.
- Specimen viewing mirror.
Mounts on upper stage for straight-on viewing of specimen.
- Easy-Lift glass knife spacer and post.
- PowerTome dust cover.
- Stereomicroscope-mounted breath shield
- Automated water level control system
Maintains constant water level in knife boat, automatically adjusting as required. For use with PTPC, PT3D, and ATUMtome.



STATIC LINE IONIZER, 110VAC or 220 - 240VAC



AUTOMATED WATER LEVEL CONTROL SYSTEM
(for use with PTPCZ, PT3D, ATUMtome)



WATER TROUGH FILLER
(PERISTALTIC WATER PUMP)